

Sun StorEdge[™] Network FC Switch-8 and Switch-16 Configuration Supplement for SAN 3.1 Disaster Tolerance Configurations

The rules for the Sun StorEdge[™] Network FC Switch-8 and Switch-16 Sun SAN 3.0 have been extended to support additional configurations for disaster recovery scenarios. This document lists the modifications to the configuration rules in the *Sun StorEdge Network FC Switch-8 and Switch-16 Sun Installation and Configuration Guide: Sun StorEdge SAN 3.0 Release.* It also provides illustrative examples to show use of the extended rules.

Extended Rules

- Servers and storage can be in the same name server zone across inter-switch links (ISLs) on separate switches. This
 enables you to have servers at the recovery site. It also means you can have local and remote storage in the same zone
 so that storage can be mirrored at both locations.
- Cascaded switches support use of short-wave as well as long-wave GBICs. Use of short-wave GBICs allows a higher port count in a local configuration. You can cascade a maximum of two switches with one ISL hop between the initiator and target, with distances between 10 meters and 10 kilometers. ISL hops do not include the connections between hosts and switches or between switches and storage.




FIGURE 1 Disaster Recovery Configuration

Explanation Of Figure 1

The follow describes FIGURE 1, which is an example of a disaster recovery configuration that spans two geographically separated sites.

Switches

The switches are cascaded in pairs with long-wave ISLs connected at their T-ports. The hosts connect to the F-ports and the arrays connect to the TL-ports on the switches. Two name server zones aggregate the F-, T-, and TL-ports configured on each pair of switches.

Servers and Arrays

Each server has four host bus adapter (HBA) ports. Two HBA ports are connected to each of the switch fabrics for high availability. The dual HBA port connections denote that the Sun StorEdge Traffic Manager provides load balance support for I/O between the host bus adapters and switches.

At each site, servers and Sun StorEdge T3 or T3+ arrays are configured in the same name server zone on each cascaded switch pair. Because local and remote storage, as well as hosts, are configured in the same zones, the SAN is mirrored at both locations.

ISLs

ISLs can use either short- or long-wave GBICs. Distance can range from 10 meters to 10 km.




FIGURE 2 Pre-configured Disaster Tolerant Fabric With Sun StorEdge T3+ Array Racks.

Explanation Of Figure 2

FIGURE 2 shows the same configuration as the one in FIGURE 1, except it does not provide port detail and uses a few more arrays. FIGURE 2 shows a disaster recovery configuration using the pre-configured and pre-wired Sun StorEdge T3 or T3+ array cabinets. Each cabinet contains two switches and multiple Sun StorEdge T3 or T3+ Enterprise System arrays pre-configured and pre-wired. The figure shows the SAN connectivity with hosts and storage at both ends of a cascaded switch configuration, where the end sites are 10 km apart. The switch port types are assumed to be set similar to those in FIGURE 1.

Related Documentation

TABLE 1	1 Documentation for the Sun StorEdge [™] Network FC Switch-8 and Switch	1-16 Sun SAN 3.0
---------	--	------------------

Product	Application	Title	Part Number
Switch	Installation/Configuration	Sun StorEdge Network FC Switch-8 and Switch-16 Sun Installation and Configuration Guide: Sun StorEdge SAN 3.0 Release	816-0830-12
SANbox	Installer/User's information	SANbox-16STD Fibre Channel Switch Installer's/User's Manual	875-3141-10
	Installer/User's information	SANbox-8 Fibre Channel Switch Installer's/ User's Manual	875-3142-10
	Installer/User's Information	SANbox 8/16 Switch Management User's Manual	875-3060-10
	Installer/User's Information	SANbox 8/16 Switch Management User's Manual	875-3143-10
	Latest Information	Sun StorEdge Network FC Switch-8 and Switch-16 Release Notes ¹	816-0842-10
	Software	CDInsert	
Arrays	Latest Information	Sun StorEdge A5000 Product Notes ¹	805-1018-13
	Latest Information	Sun StorEdge T3 Disk Tray Release1 Notes	806-1497-12
	Late news - Best Practices	Sun StorEdge A3x00/A3500 FC Best Practices Guide	806-6419-10
	Latest Information	Sun StorEdge A3500FC Release Notes ¹	805-7758-11
Other Components	Sun StorEdge T3 Array/ Switch	Sun StorEdge T3Array to Sun StorEdge Network FC Switch Configuration Guide	816-2096-10
	Traffic Management	Sun StorEdge Traffic Manager Installation and Configuration Guide	816-1420-10
Storage Cabinet	Rackmount information Online	Rackmount Placement Matrix	805-4748-xx
Software	RAID software	Sun StorEdge RAID Manager 6.22 User's Guide	806-0478-10
manpage	cfgadm utility	cfgadm_fp	

1. Check for the latest updates at http://sunsolve.sun.com.

Accessing Sun Documentation Online

The Sun StorEdge Network FC Switch-8 and Switch-16 Sun Installation and Configuration Guide: Sun StorEdge SAN 3.0 Release and a broad selection of Sun system documentation is located at:

```
http://www.sun.com/products-n-solutions/hardware/docs
```

A complete set of Solaris documentation and many other titles are located at:

http://docs.sun.com

Sun Welcomes Your Comments

Sun is interested in improving its documentation and welcomes your comments and suggestions. You can E-mail your comments to Sun at:

docfeedback@sun.com

Please include the part number (816-3652-10) of the document in the subject line of your E-mail.

Copyright 2001 Sun Microsystems, Inc. All rights reserved. Use is subject to license terms. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers. Sun, Sun Microsystems, the Sun logo, AnswerBook2, docs.sun.com, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

Copyright 2001 Sun Microsystems, Inc. Tous droits réservés. Distribué par des licences qui en restreignent l'utilization. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun. Sun, Sun Microsystems, le logo Sun, AnswerBook2, docs.sun.com, et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unit et dans d'autres pays.



Sun Microsystems, Inc., 901 San Antonio Road, Palo Alto, CA 94303-4900 U.S.A., 650 960-1300, Fax 650 969-9131

